

OGL 1000/000

GREASE

High Performance Sprayable Grease For Lubrication of Open Gears

Applications

ASV OGL 1000/000 is a non-hardening, sprayable, adhesive grease designed for lubrication and protection of tooth flanks of large open gears exposed to extremely high loads and temperatures.

ASV OGL 1000/000 is based on highly viscous mineral oils thickened with an aluminum complex soap thickener with a high content of ultra-fine graphite and select extreme pressure and anti-wear additives.

ASV OGL 1000/000 ensures excellent resistance to shock loading and prevents danger of damage to tooth flanks by continually maintaining a boundary lubricating film between frictional points of mating surfaces.

ASV OGL 1000/000 clings tenaciously to gear tooth flanks and does not squeeze out under high loads and pressures.

ASV OGL 1000/000 is capable of withstanding extreme operating and environmental conditions and protects surface from corrosion and can be easily pumped via spray systems on to the gear teeth.

Applications

For spray lubrication of open gears in:

- Heavy engineering industries
- Cement, gypsum and lime manufacturing equipment
- Mining and earth moving equipment
- Wood working equipment
- Sugar mill machinery

For lubrication and wear protection of:

- Highly stressed large open gears and slew ring gears
- Large chains
- Wire ropes
- Guide rails

Benefits

- Wide service temperature range of -10°C to +180°C
- Thermally stable within -30°C +250°C
- Excellent adhesion to metal surfaces
- Forms a non-hardening, adhesive film over gear tooth flanks capable of withstanding high pressures
- Excellent load carrying capacity under severe conditions
- Very good resistance to water and water washout
- Contains additives to prevent against degradation by rust, corrosion and oxidation
- Easily sprayable through spraying systems
- Free of bitumen, chlorine, lead, toxic heavy metals or hazardous solvents

Directions for Use

Use as supplied. Never dilute or mix with oil or grease. Apply on all clean sliding surfaces by normal greasing methods i.e. by brush, grease gun or dispense via centralized lubrication systems. Replace cover after use.

OGL 1000/000

GREASE

TECHNICAL PROPERTIES			
PARAMETER	VALUE	UNIT	METHOD
Appearance	Smooth grease		Visual
Color	Black		Visual
Base oil	Mineral / synthetic		In house
Base oil viscosity @ 40°C	~ 1000	mm ² /s	ASTM D 445
Thickener	Aluminum complex		In house
Penetration, worked	445-475	mm/10	ASTM D 217
NLGI consistency	000	Class	DIN 51 818
Water washout	< 1	% wt. loss	ASTM D 1264
Copper strip corrosion	1b	Rating	ASTM D 4048
Rust prevention	Pass		ASTM D 1743
Lubricating solid	Ultrafine graphite		In house
Four ball test, weld load	700	kg	ASTM D 2596
FZG test, damage load stage	≥ 12		DIN 51 354
Service temperatures	-10 to +180 (thermal stability to +250)	°C	

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

Available Packaging

180 kg

Shelf Life

36 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.