

VALV KOTE® 390 GREASE

Gate Valve Seat Sealant & Body Fill Grease

Product Description

Valv-Kote 390 valve sealant and body filler grease is a proprietary valve sealing lubricant formulated using chemically resistant oils thickened with an inorganic soap thickener and is suitable for use as valve sealant for service where resistance to gaseous and liquid hydrocarbons is required. Also known as 'peanut butter' type grease, it is suitable for expanding gate type valves.

Valv-Kote 390 exhibits good sealing qualities, corrosion resistance and protects against metal to metal contact to prevent galling.

Benefits

- Good mechanical stability
- Excellent temperature stability
- Good oxidation stability
- Biodegradable
- Offers corrosion protection
- Stop leaks
- Does not contain any hazardous products and is non-toxic
- Highly adhesive
- Water resistant
- Soft malleable pumpable consistency
- Cleanup is easy with a wide range of industrial solvents
- Prevents wear due to friction and stops scoring and galling
- Reduces torque

Directions for Use

Use as supplied. Never dilute or mix with other oil or grease. Can be cleaned using any regular solvents such as alcohols, ketones, chlorinated.

VALV KOTE® 390 GREASE

TECHNICAL PROPERTY

Parameter	Value
Appearance	Smooth paste
Color	Tan brown
Base Oil	Proprietary
Thickener	Inorganic
Penetration, ASTM D 217	270-290
Specific Gravity @ 20°C	1.29-1.31
Drop Point, °C ASTM D 2265	None
Oil Separation, % by wt., ASTM D 6184	<5
Service Rating, °C	-18 to +121
Recommended For	<ul style="list-style-type: none">▪ Crude Oil▪ Petroleum Liquids▪ Dilute Acids & Bases▪ Salt Water <ul style="list-style-type: none">▪ Organic Condensates▪ Petroleum Gases▪ Aqueous Solutions
Not Recommended For	<ul style="list-style-type: none">▪ Oxygen▪ Strong Oxidizers

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

Available Packaging

20 kg, 180 kg

Shelf Life

36 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK® SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.