

1825 SPRAY

FAST AIR DRYING MoS₂ DRY FILM LUBRICANT

Applications

- As a dry film lubricant for components exposed to abrasive or dusty environments as threaded connections, pins, levers, pivots, splines, bolts, chains.
- As a metal pretreatment lubricant prior to assembly for effective running in to reduce wear, friction and eliminate metal to metal contact and seizure.
- As a lubricant for components exposed to critical environmental conditions as vacuums, radiation, high temperatures, humidity.
- As a heavy duty, high temperature thread compound to prevent seizure and corrosion and facilitate easy assembly and non-destructive disassembly.
- As an anti-friction coating for metal cutting tools as millers, reamers, taps, drills, gear cutters, punches, dies to prevent sticking, binding and metal build up; increase life of tools, production quality and efficiency.
- As an extreme pressure lubricant for heavily loaded or stressed surfaces to prevent wear, friction, galling, scuffing, seizure and fretting as for press fits, pins, levers, pivots, gears, splines, journals, linkages.

Benefits

- Extremely wide service temperature range of -180°C to +450°C
- Low coefficient of friction, high surface load and pressure withstanding capacity
- High and low temperature performance
- Protects surfaces from wear, galling and seizure
- Oil, grease and solvent resistant
- Prevents stick-slip and fretting corrosion
- Provides clean dry film lubrication and does not accumulate dirt or abrasives
- Offers surface protection from corrosion
- Lubricates under adverse operating environments such as in vacuum or near radiation
- Provides maintenance free permanent lubrication where oil or grease contamination cannot be tolerated
- Excellent lubricity and highly abrasion resistant
- Increases service life of equipment

Directions for Use

Shake the can vigorously for a couple of minutes before spraying till the bearing noise from inside the container is audible. Repeat before every application. Spray onto a clean, dry and degreased surface. Only a thin film of this lubricant is required. Allow solvents to evaporate. Spray from a distance of 20-30 cms. Repeat if necessary. Excess lubricant may fall off during assembly. For cleaning the valve dip-tube after spraying, invert the can and depress the actuator button for a few short bursts till only the clear propellant comes out.

Caution (aerosol)

Contains flammable solvents and propellant. Do not spray near naked flame, hot surfaces or energized equipment. Use with adequate ventilation.

1825 SPRAY

TECHNICAL PROPERTIES	
PARAMETER	VALUE
Type	Powder
Appearance	Free flowing, lump free microfine solid particles
Color	Gray black
Density, g/cc	4.8
Purity	98.5 %
Average particle size, μm	2.5 – 5
Magnetic properties	Non magnetic
Load bearing capacity	Exceeds yield point of most known metals
Special properties	Lubricates under pressures exceeding 500,000 psi. Unaffected by liquid oxygen, vacuum and suitable for use near radioactive areas Non conductive Confirms to Military specifications MIL-M-7866
Service temperature range, °C	-185 to +450 under normal conditions (up to +1100 under vacuum conditions)
Propellant (aerosol)	Non CFC

General

Use in well ventilated areas. Avoid continuous breathing of vapor and spray mist. In closed areas or areas with poor ventilation, use respiratory protection. For complete details on safety, short and long term exposure, refer to this product's safety data sheet (SDS).

Disposal

All used and unused product should be disposed of in accordance with state regulations.

Handling

Read instructions on the container label of the product before use. The product safety data sheet (SDS) contains the relevant information regarding personal protective equipment, safe use, physical and health hazards. Safety data sheet is available from ASV or your local ASV distributor.

Available Packaging

500 ml aerosol spray

Shelf Life

24 months from date of manufacture in sealed condition.

Limited Warranty

The information and data contained in this sheet is accurate to the best of our knowledge or is obtained from sources, tests or experiences believed by us to be reliable and accurate. User is responsible for determining whether recommended ASV product is fit for a particular purpose. All products should be tested for suitability on a particular application prior to actual use. We make no representations of any kind. Data offered without warranty. Product manufactured is for industrial use only.

Manufactured by
ASV Multichemie Private Limited
W 46, TTC Industrial Area, MIDC Rabale,
Navi Mumbai 400 701 INDIA
Contact: +91 22 2764 2516
Email: info@asvmultichemie.com

WWW.ASVMULTICHEMIE.COM

ASV® MOLYSULF® PENETROIL® SHINY GALVA® VALV-KOTE® BRIGHT ZINK®
SPEZET® MOLYCHEM® TRIBOSULF® are Registered Trademarks of ASV MULTICHEMIE
PRIVATE LIMITED, INDIA.
ALL DATA OFFERED WITHOUT LIABILITY OR WARRANTY.